



LES GAZ INDUSTRIELS LTD.

UNE VALEUR SÛRE

Est. 1952

OXYGEN MATERIAL SAFETY DATA SHEET

DATE: April 2001

1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION

Product Name	OXYGEN
Chemical Formula	O ₂
Trade Names	Oxygen, Compressed Oxygen, Instrument Grade (N2.5) Oxygen, EP Grade (N2.7) Oxygen, IG Zero (N4.5) Oxygen, UHP (N4.5) Medical Oxygen
Colour Coding.	Compressed, IG, EP, IG Zero and UHP cylinders all have black bodies. The relevant decals or stencilling depict the actual grades. Medical Oxygen
Valves	Black Body with a white shoulder. Compressed, IG, EP, IG Zero and Medical grades have 3 SO- Brass, 5/8 inch BSP right hand female valves. Medical oxygen cylinders could also have the revenant Pin Index valves fitted UHP grade has the Neriki-Brass 5/8 inch BSP right hand female valve fitted.
Company Identification	Les Gaz Industriels Ltd Pailles Road G.R.N.W. – Republic of Mauritius Tel. No: (+230) 212 8306 Fax No: (+230) 212 0235

2 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Oxygen
Chemical Family	Oxidant
CAS No.	7782-44-7
UN No.	1072
ERG No.	122
Hazchem Warning	5 A Non-flammable gas

3 HAZARDS IDENTIFICATION

Main Hazards	All cylinders are portable gas containers, and must be regarded as pressure vessels at all times. Oxygen is non-flammable, but readily supports combustion. Never permit oil, grease or other readily combustible substance to come into contact with high concentrations of Oxygen.
Adverse Health Effects	Central nervous system toxicity including dizziness, convulsions and loss of consciousness can occur after only 2-3 hours of exposure to pure oxygen at 2 or more atmospheres. Retrosternal soreness, associated with coughing and breathing difficulties, made worse by smoking and exposure to cold air can occur after breathing pure oxygen at atmospheric pressure for several hours.
Chemical Hazards	Oxygen is non-flammable, but strongly supports combustion (including some materials which do not normally burn in air). Since dry Oxygen is non-corrosive, most materials of construction are suitable. Avoid all flammable materials.
Biological Hazards	No known effect.
Vapour Inhalation	Pure oxygen is a local irritant to mucous membranes and, with extended continued exposure, can be destructive to lung tissue.
Eye Contact	No known effect.
Skin Contact	No known effect.
Ingestion	No known effect.

4 FIRST AID MEASURES

Prompt medical attention is mandatory in all cases of overexposure to Oxygen. Rescue personnel should be cognisant of extreme fire hazard associated with oxygen-rich atmospheres. Conscious persons should be assisted to an uncontaminated area and inhale fresh air. They should be kept warm and quiet. Quick removal from the contaminated area is most important. The physician should be informed that the patient has experienced hyperoxia.

Eye Contact	No known effect.
Skin Contact	No known effect.
Ingestion	No known effect.

5 FIRE FIGHTING MEASURES

Extinguishing media	As Oxygen is non-flammable, but strongly supports combustion, the correct type of extinguishing should be used depending on the combustible material involved.
Specific Hazards	Oxygen vigorously accelerates combustion. Materials that would not normally burn in air could combust vigorously in atmospheres having high concentrations of Oxygen.
Emergency Actions	If possible, shut off the source of escaping Oxygen. Evacuate area. All cylinders should be removed from the vicinity of the fire. Cylinders that cannot be removed should be cooled with water from a safe distance. Cylinders which have been exposed to excessive heat should be clearly identified and returned to supplier. CONTACT THE NEAREST AFROX BRANCH.
Protective Clothing	Safety goggles, gloves and safety shoes should be worn when handling cylinders.
Environmental precautions.	As the gas is heavier than air, pockets of Oxygen-enriched air could occur. These could lead to the fire spreading rapidly. If possible, ventilate the affected area.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions	Although Oxygen is not itself combustible, it supports and accelerates combustion. Clothes and other materials, not normally considered flammable, will burn fiercely in the presence of Oxygen, and can be set alight by a single spark, or even hot cigarette ash.
Environmental precautions	Oxygen does not pose a hazard to the environment. Beware of Oxygen-enriched atmospheres coming into contact with readily combustible materials.
Small spills	Shut off the source of excess Oxygen. Ventilate the area.
Large spills	Evacuate the area. Shut off the source of the spill if this can be done without risk. Ventilate the area using forced-draught if necessary.

7 HANDLING AND STORAGE

Do not allow cylinders to slide or come into contact with sharp edges. Cylinders of Oxygen should not be stored near cylinders of acetylene or other combustible gases. Oxygen cylinders may be stacked horizontally provided that they are firmly secured at each end to prevent rolling. Prevent dirt, grit of any sort, oil or any other lubricant from entering the cylinder valves, and store cylinders well clear of any corrosive influence, e.g. battery acid. Compliance with all relevant legislation is essential. Use a "first in - first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Keep out of reach of children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Hazards	Avoid exposure to oxygen-enriched atmospheres, as this could result in clothing becoming saturated by oxygen. On ignition the clothing could burn fiercely resulting in serious burns.
Engineering control measures	Engineering control measures are preferred to reduce exposure to Oxygen-enriched atmospheres. General methods include forced-draught ventilation, separate from other exhaust ventilation systems. Ensure that sufficient fresh air enters at, or near, floor level.
Personal protection	Safety goggles, gloves and shoes should be worn when handling cylinders.
Skin	No known effect.

9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DATA

Chemical Symbol	O ₂
Molecular Weight	32,00
Specific Volume @ 20°C & 101,325 kPa	755 ml/g
Density, gas @ 101,325 kPa and 20°C	1,33 kg/m ³
Relative density (Air = 1) @ 101,325 kPa	1,053
Colour	None
Taste	None
Odour	None

10 STABILITY AND REACTIVITY

Conditions to avoid	The build-up of Oxygen-enriched atmospheres as, depending on temperature, oxygen reacts with all of the elements, excepting the inert gases, to form oxides. These reactions can sometimes be violent, as with highly combustible materials such as oil and grease. Never use cylinders as rollers or supports, or for any other purpose than the storage of Oxygen. Never expose cylinders to excessive heat, as this may cause sufficient build-up of pressure to rupture the cylinders.
Incompatible Materials	Since dry Oxygen is non-corrosive, most materials of construction are suitable. Avoid all flammable materials. (For further information see Section 3, Chemical Hazards).

Hazardous Decomposition Products -None

11 TOXICOLOGICAL INFORMATION

Acute Toxicity	No known effect.
Skin & eye contact	No known effect.
Chronic Toxicity	No known effect.
Carcinogenicity	No known effect.
Mutagenicity	No known effect.
Reproductive Hazards	No known effect

(For further information see Section 3. Adverse Health Effects).

12 ECOLOGICAL INFORMATION

Oxygen is heavier than air and care should be taken to avoid the formation of Oxygen-enriched pockets. It does not pose a hazard to the ecology.

13 DISPOSAL CONSIDERATIONS

Disposal Methods	Small amounts may be blown to the atmosphere under controlled conditions. Large amounts should only be handled by the gas supplier.
Disposal of packaging	The disposal of containers must only be handled by the gas supplier.

14 TRANSPORT INFORMATION

ROAD TRANSPORTATION

UN No.	1072
ERG No	122
Hazchem warning	5A Non-flammable gas

SEA TRANSPORTATION

IMDG	1072
------	------

Class	
Packaging group	
Label	Non-flammable gas

AIR TRANSPORTATION

ICAO/IATA Code	1072
Class	Non-flammable
Packaging group	2.2

Packaging instructions

- Cargo	200
- Passenger	200
Maximum quantity allowed	
- Cargo	100kg
- Passenger	75kg

15 REGULATORY INFORMATION

EEC Hazard class	Non-flammable
Risk phrases	R8 Contact with combustible material may cause fire R37 Irritating to respiratory system R 44 Risk of explosion if heated under confinement. R48 Danger of serious damage to health by prolonged exposure.
Safety phrases	S2 Keep out of reach of children S9 Keep container in a well-ventilated place S15 Keep away from heat S21 When using do not smoke S27 Take off immediately all contaminated clothing.
National Legislation:	None
Refer to SABS 0265 for explanation of the above.	

16 OTHER INFORMATION

Bibliography
Compressed Gas Association, Arlington, Virginia
Handbook of Compressed Gases - 3rd Edition
Matheson. Matheson Gas Data Book - 6th Edition

17 EXCLUSION OF LIABILITY

Information contained in this publication is accurate at the date of publication. The company does not accept liability arising from the use of this information, or the use, application, adaptation or process of any products described herein.

A member of The AFROX Group
For product and safety enquiries please phone

EMERGENCY N°:

+230 800 1133 (business hours)

+230 212 8306 (business hours)

+230 5421 5944 (24 hours)

+230 5729 3846 (24 hours)

+230 5729 3845 (24 hours)

+230 5421 1511 (24 hours)

+230 5497 5432 (24 hours)

+230 5421 9526 (24 hours)